

# F 100

Forward  
vibratory plate



## For compaction of sand, gravel, rock fill and paving stones.

All our machine models are versatile and easy to operate. They are also durable and reliable, which means lower operating and maintenance costs.

- The Swebpac F 100 is the ideal high performance all-round machine.
- Cyclone pre-cleaner air filter, improves dust filtering efficiency and lowers maintenance cost.
- With a Vulkollan® plate (accessory) attached to the base, it can compact paved areas efficiently for an even surface.
- The machine can cope with the toughest of jobs since parts of the motor and transmission are fully enclosed in a rugged polythene casing. The chassis and handle are hot-dip galvanized and maintenance-free.
- The excentric element has permanently lubricated bearings that require no maintenance.
- The handle bar can easily be removed without any tools, for instance, for transportation.

Swebpac is Sweden's leading manufacturer of soil compactors. The company has a wide range of products, with different motor options and a variety of sizes for every application. Swebpac is certified for quality and environmental management under ISO 9001 and 14001, and our machines are Eurotest-certified by SMP Swedish Machinery Testing Institute. You will find detailed information about the company and our products on our website, [www.swebpac.com](http://www.swebpac.com). We reserve the right to make changes in technical specifications without prior notice.

Swebpac AB  
Blockvägen 3 | SE-341 32 Ljungby | Sweden  
Tel +46 (0)372-156 00 | [www.swebpac.com](http://www.swebpac.com)

## TECHNICAL DATA SWE PAC F 100

Weight, net	97 kg
Base plate, width x length	380x580 mm
Height, max	1050 mm
Length, max	1000 mm
Engine	Yanmar L48
Fuel tank capacity	2.4 liter
Fuel	Diesel
Engine output, max	3.5 kW (4.7 hp)
Centrifugal force	15 kN
Frequency	88 Hz
Working speed	0 - 25 m/min
Hand/arm vibrations HAV according to ISO 5349 on gravel surface	4.6 m/s <sup>2</sup>
Guaranteed sound-power level, L <sub>WA</sub>	105 dB(A)
Sound pressure level (at operator's ear), OP	90 dB(A)

## Part number

305800 F 100 with Yanmar diesel engine

## Accessories

305322 Vulkollan plate complete