

F 75E

Forward vibratory plate



For compaction of sand, gravel, rock fill and paving stones.

All our machine models are versatile and easy to operate. They are also durable and reliable, which means lower operating and maintenance costs.

- The Swepac F 75E is a 75 kg vibratory plate characterized by its compact, robust design, low maintenance requirements and thus low operating costs.
- The machine is powered by a single-phase electric motor plugged into a grounded wall outlet. Since the motor emits no exhaust fumes, the machine can be used in poorly ventilated spaces as well as indoors.
- The F 75E is suitable for smaller jobs, such as modifying the subsurface for pavers. With a Vulkollan® plate (accessory) attached to the base, it can compact paved areas efficiently for an even surface.
- The machine can cope with the toughest of jobs since parts of the motor and transmission are fully enclosed in a rugged polythene casing. The chassis and handle are hot-dip galvanized and maintenance-free. The eccentric element has permanently lubricated bearings.
- The handle bar can easily be removed without any tools, for instance, for transportation.

Swepac is Sweden's leading manufacturer of soil compactors. The company has a wide range of products, with different motor options and a variety of sizes for every application. Swepac is certified for quality and environmental management under ISO 9001 and 14001, and our machines are Eurotest-certified by SMP Swedish Machinery Testing Institute. You will find detailed information about the company and our products on our website, www.swepac.com. We reserve the right to make changes in technical specifications without prior notice.

Swepac AB
Blockvägen 3 | SE-341 32 Ljungby | Sweden
Tel +46 (0)372-156 00 | www.swepac.com

TECHNICAL DATA SWEPAC F 75E

Weight, net	75 kg
Base plate, width	380 mm
Height, max / min	1000 / 920 mm
Length, max / min	920 / 600 mm
Engine	EI 1-phase, 230 V
Engine output, max	1.1 kW
Centrifugal force	11 kN
Frequency	88 Hz
Working speed	0 - 25 m/min
Hand/arm vibrations HAV according to ISO 5349 on gravel surface	4.6 m/s ²
Guaranteed sound-power level, L _{WA}	103 dB(A)
Sound pressure level (at operator's ear), OP	90 dB(A)

Part number

305150 F 75E with 230V electric motor

Accessories

305138 Vulkollan plate complete

F75E_2016-02_GB

swepac